

MC1000 Series (0 to +75°C)
 MC1200 Series (-55 to +125°C)

The MECL II series of monolithic integrated logic circuits presents the system design engineer with an integrated circuit family designed to permit system implementation with the fewest possible number of individual units. This approach offers cost savings, reduced power supply requirements, smaller physical size and high reliability.

MECL II circuits feature the fastest propagation delay times with commensurate rise and fall times of any family of integrated circuits. This feature plus the constant current feature of MECL imposes fewer restrictions on design, layout and system fabrication than any other high-speed family.

FEATURES

- Propagation typically 4 ns per logic decision
- Excellent noise immunity characteristics
- Simultaneous OR/NOR outputs
- High fan-in and fan-out capabilities
- Internally temperature compensated



**F SUFFIX
 CERAMIC PACKAGE
 CASE 607**



**L SUFFIX
 CERAMIC PACKAGE
 CASE 620**




**L SUFFIX
 CERAMIC PACKAGE
 CASE 632
 TO-116**



**P SUFFIX
 PLASTIC PACKAGE
 CASE 646**



**P SUFFIX
 PLASTIC PACKAGE
 CASE 648**



**F SUFFIX
 CERAMIC PACKAGE
 CASE 650**

FUNCTIONS AND CHARACTERISTICS (V_{CC} = 0, V_{EE} = -5.2 V, T_A = 25°C)

| Function | Type ① | | Loading Factor Each Output | Propagation Delay ns typ | Power Dissipation mW typ/pkg | Case |
|--|---------------|------------|----------------------------|--------------------------|------------------------------|-------------|
| | -55 to +125°C | 0 to +75°C | | | | |
| Single 6-Input Gate, 3 OR Outputs w/Pulldowns 3 NOR Outputs w/Pulldowns | MC1201F,L | MC1001P | 25 | 4.0 | 115 | 607,632,646 |
| Dual 4-Input Gate, 2 OR Outputs w/Pulldowns 2 NOR Outputs w/Pulldowns | MC1204F,L | MC1004P | 25 | 4.0 | 95 | 607,632,646 |
| Dual 4-Input Gate, 2 OR Outputs w/o Pulldowns 2 NOR Outputs w/o Pulldowns | MC1206F,L | MC1006P | 25 | 4.0 | 45 | 607,632,646 |
| Triple 3-Input Gate, 3 NOR Outputs w/Pulldowns | MC1207F,L | MC1007P | 25 | 4.0 | 110 | 607,632,646 |
| Quad 2-Input Gate, 4 NOR Outputs w/Pulldowns | MC1210F,L | MC1010P | 25 | 4.5 | 115 | 607,632,646 |
| Quad 2-Input Gate, 2 NOR Outputs w/Pulldowns 2 NOR Outputs w/o Pulldowns | MC1211F,L | MC1011P | 25 | 4.5 | 95 | 607,632,646 |

① Type numbers with F suffix use Case 607 or 650, Type numbers with L suffix use Case 632 or 620 as indicated. Type numbers with P suffix use Case 646 or 648 as indicated.