

## DM74LS503 8-Bit Successive Approximation Register (with Expansion Control)


### General Description

The 'LS503 register is basically the same as the 'LS502 except that it has an active LOW Enable ( $\bar{E}$ ) input that is used in cascading two or more packages for longer word lengths. A HIGH signal on  $\bar{E}$ , after a START operation, forces Q7 HIGH and prevents the device from accepting serial data. With the  $\bar{E}$  input of an 'LS503 connected to the  $\overline{CC}$  output of a preceding (more significant) device, the 'LS503 will be inhibited until the preceding device is filled, causing its  $\overline{CC}$  output to go LOW. This LOW signal then enables the 'LS503 to accept the serial data on subsequent clocks. For a description of the starting, shifting and conversion operations, please see the 'LS502 data sheet.


### Features

- Performs serial-to-parallel conversion
- Expansion control for longer words
- Storage and control for successive approximation A to D conversion
- Low power Schottky version of 2503

### Connection Diagram



### Logic Symbol



V<sub>CC</sub> = Pin 16  
GND = Pin 8

Order Number DM54LS503J, DM54LS503W,  
DM74LS503WM or DM74LS503N  
See Package Number J16A, M16B, N16E or W16A

Pin Names	Description
D	Serial Data Input
$\bar{S}$	Start Input (Active LOW)
CP	Clock Pulse Input (Active Rising Edge)
$\bar{E}$	Conversion Enable Input (Active LOW)
$\overline{CC}$	Conversion Complete Output (Active LOW)
Q0–Q7	Parallel Register Outputs
$\bar{Q}7$	Complement of Q7 Output

## Absolute Maximum Ratings (Note 1)

Supply Voltage	7V	DM54LS	-55°C to +125°C
Input Voltage	7V	DM74LS	0°C to +70°C
Operating Free Air Temperature Range		Storage Temperature Range	-65°C to +150°C

## Recommended Operating Conditions

Symbol	Parameter	DM54LS503			DM74LS503			Units
		Min	Nom	Max	Min	Nom	Max	
V <sub>CC</sub>	Supply Voltage	4.5	5	5.5	4.75	5	5.25	V
V <sub>IH</sub>	High Level Input Voltage	2			2			V
V <sub>IL</sub>	Low Level Input Voltage			0.7			0.8	V
I <sub>OH</sub>	High Level Output Current			-0.4			-0.4	mA
I <sub>OL</sub>	Low Level Output Current			4			8	mA
T <sub>A</sub>	Free Air Operating Temperature	-55		125	0		70	°C
t <sub>s</sub> (H)	Setup Time HIGH or LOW	5			16			ns
t <sub>s</sub> (L)	$\bar{S}$ to CP	5			16			ns
t <sub>h</sub> (H)	Hold Time HIGH or LOW	5			0			ns
t <sub>h</sub> (L)	$\bar{S}$ to CP	5			0			ns
t <sub>s</sub> (H)	Setup Time HIGH or LOW	5			8			ns
t <sub>s</sub> (L)	D to CP	5			8			ns
t <sub>h</sub> (H)	Hold Time HIGH or LOW	5			10			ns
t <sub>h</sub> (L)	D to CP	5			10			ns
t <sub>w</sub> (H)	CP Pulse Width HIGH or LOW	20			46			ns
t <sub>w</sub> (L)		20			46			ns

**Note 1:** The "Absolute Maximum Ratings" are those values beyond which the safety of the device cannot be guaranteed. The device should not be operated at these limits. The parametric values defined in the "Electrical Characteristics" table are not guaranteed at the absolute maximum ratings. The "Recommended Operating Conditions" table will define the conditions for actual device operation.

## Electrical Characteristics

Over recommended operating free air temperature range (unless otherwise noted)

Symbol	Parameter	Conditions	Min	Typ (Note 2)	Max	Units
V <sub>I</sub>	Input Clamp Voltage	V <sub>CC</sub> = Min, I <sub>I</sub> = -18 mA			-1.5	V
V <sub>OH</sub>	High Level Output Voltage	V <sub>CC</sub> = Min, I <sub>OH</sub> = Max, V <sub>IL</sub> = Max	DM54 2.5			V
V <sub>OL</sub>	Low Level Output Voltage	V <sub>CC</sub> = Min, I <sub>OL</sub> = Max, V <sub>IH</sub> = Min	DM54		0.4	V
			DM74		0.5	
		I <sub>OL</sub> = 4 mA, V <sub>CC</sub> = Min	DM74		0.4	
I <sub>I</sub>	Input Current @ Max Input Voltage	V <sub>CC</sub> = Max, V <sub>I</sub> = 7V	DM74		0.1	mA
		V <sub>I</sub> = 10V	DM54			
I <sub>IH</sub>	High Level Input Current	V <sub>CC</sub> = Max, V <sub>I</sub> = 2.7V			20	μA
I <sub>IL</sub>	Low Level Input Current	V <sub>CC</sub> = Max, V <sub>I</sub> = 0.4V			-0.8	mA
I <sub>OS</sub>	Short Circuit Output Current	V <sub>CC</sub> = Max (Note 3)	DM54	-20	-100	mA
			DM74	-20	-100	
I <sub>CC</sub>	Supply Current	V <sub>CC</sub> = Max			65	mA

**Note 2:** All typicals are at V<sub>CC</sub> = 5V, T<sub>A</sub> = 25°C.


**Note 3:** Not more than one output should be shorted at a time, and the duration should not exceed one second.

## Switching Characteristics

$V_{CC} = +5.0V$ ,  $T_A = +25^\circ C$


Symbol	Parameter	DM54LS503		DM74LS503		Units
		$R_L = 2\text{ k}\Omega$ , $C_L = 15\text{ pF}$				
		Min	Max	Min	Max	
$f_{max}$	Maximum Count Frequency	25		15		MHz
$t_{PLH}$	Propagation Delay		35		35	ns
$t_{PHL}$	CP to Qn or $\overline{CC}$		25		25	
$t_{PLH}$	Propagation Delay		20		20	ns
$t_{PHL}$	$\overline{E}$ to Q7		24		24	

## Logic Diagram




Note: Cell logic is repeated for register stages Q5 to Q1.


### Connection for Longer Word Lengths



**Physical Dimensions** inches (millimeters) unless otherwise noted




**16-Lead Ceramic Dual-In-Line Package (J)**  
**Order Number DM54LS503J**  
**Package Number J16A**




**16-Lead Wide Small Outline Molded Package (M)**  
**Order Number DM74LS503WM**  
**Package Number M16B**

**Physical Dimensions** inches (millimeters) unless otherwise noted (Continued)



**16-Lead Molded Dual-In-Line Package (N)**  
 Order Number DM74LS503N  
 Package Number N16E



**16-Lead Ceramic Flat Package (W)**  
 Order Number DM54LS503W  
 Package Number W16A