FAIRCHILD
SEMICONDUCTOR TM

KSC2258/2258A

High Voltage General Amplifier
TV Video Output Amplifier

- High BV_{CEO}



TO-126

1. Emitter 2.Collector 3.Base

NPN Epitaxial Silicon Transistor

Absolute Maximum Ratings T_C=25°C unless otherwise noted

Symbol	Parameter	Value	Units
V_{CBO}	Collector-Base Voltage		
	: KSC2258	250	V
	: KSC2258A	300	V
V_{CEO}	Collector-Emitter Voltage		
	: KSC2258	250	V
	: KSC2258A	300	V
V_{EBO}	Emitter-Base Voltage	6	V
I_C	Collector Current (DC)	100	mA
I_{CP}	Collector Current (Pulse)	150	mA
P_C	Collector Dissipation (T_C=25°C)	4	W
T_J	Junction Temperature	150	°C
T_{STG}	Storage Temperature	- 55 ~ 150	°C

Electrical Characteristics T_C=25°C unless otherwise noted

Symbol	Parameter	Test Condition	Min.	Typ.	Max.	Units
BV_{EBO}	Emitter-Base Breakdown Voltage	I_E = 0.1mA, I_C = 0	6			V
I_{CER}	Collector Cut-off Current	V_{CE} = 250V, R_{BE} = 100KΩ			100	μA
h_{FE1}	DC Current Gain	V_{CE} = 20V, I_C = 40mA	40			
h_{FE2}		V_{CE} = 50V, I_C = 5mA	30			
V_{CE}(sat)	Collector-Emitter Saturation Voltage	I_C = 50mA, I_B = 5mA			1.2	V
V_{BE}(on)	Base-Emitter On Voltage	V_{CE} = -20V, I_C = 40mA			1.2	V
f_T	Current Gain Bandwidth Product	V_{CE} = 10V, I_C = 10mA		100		MHz
C_{ob}	Output Capacitance	V_{CB} = 50V, f = 1MHz		3	4.5	pF

Typical Characteristics



Figure 1. Static Characteristic



Figure 2. DC current Gain



Figure 3. Collector-Emitter Saturation Voltage



Figure 4. Collector Output Capacitance



Figure 5. Current Gain Bandwidth Product



Figure 6. Power Derating

Package Demensions

TO-126



Dimensions in Millimeters

TRADEMARKS

The following are registered and unregistered trademarks Fairchild Semiconductor owns or is authorized to use and is not intended to be an exhaustive list of all such trademarks.

ACEx™
Bottomless™
CoolFET™
CROSSVOLT™
E^2CMOS™
FACT™
FACT Quiet Series™
FAST®
FASTr™
GTO™
HiSeC™
ISOPLANAR™
MICROWIRE™
POP™
PowerTrench®
QFET™
QS™
Quiet Series™
SuperSOT™-3
SuperSOT™-6
SuperSOT™-8
SyncFET™
TinyLogic™
UHC™
VCX™

DISCLAIMER

FAIRCHILD SEMICONDUCTOR RESERVES THE RIGHT TO MAKE CHANGES WITHOUT FURTHER NOTICE TO ANY PRODUCTS HEREIN TO IMPROVE RELIABILITY, FUNCTION OR DESIGN. FAIRCHILD DOES NOT ASSUME ANY LIABILITY ARISING OUT OF THE APPLICATION OR USE OF ANY PRODUCT OR CIRCUIT DESCRIBED HEREIN; NEITHER DOES IT CONVEY ANY LICENSE UNDER ITS PATENT RIGHTS, NOR THE RIGHTS OF OTHERS.

LIFE SUPPORT POLICY

FAIRCHILD'S PRODUCTS ARE NOT AUTHORIZED FOR USE AS CRITICAL COMPONENTS IN LIFE SUPPORT DEVICES OR SYSTEMS WITHOUT THE EXPRESS WRITTEN APPROVAL OF FAIRCHILD SEMICONDUCTOR INTERNATIONAL.

As used herein:

1. Life support devices or systems are devices or systems which, (a) are intended for surgical implant into the body, or (b) support or sustain life, or (c) whose failure to perform when properly used in accordance with instructions for use provided in the labeling, can be reasonably expected to result in significant injury to the user.

2. A critical component is any component of a life support device or system whose failure to perform can be reasonably expected to cause the failure of the life support device or system, or to affect its safety or effectiveness.

PRODUCT STATUS DEFINITIONS

Definition of Terms

Datasheet Identification	Product Status	Definition
Advance Information	Formative or In Design	This datasheet contains the design specifications for product development. Specifications may change in any manner without notice.
Preliminary	First Production	This datasheet contains preliminary data, and supplementary data will be published at a later date. Fairchild Semiconductor reserves the right to make changes at any time without notice in order to improve design.
No Identification Needed	Full Production	This datasheet contains final specifications. Fairchild Semiconductor reserves the right to make changes at any time without notice in order to improve design.
Obsolete	Not In Production	This datasheet contains specifications on a product that has been discontinued by Fairchild semiconductor. The datasheet is printed for reference information only.

KSC2258A
NPN Epitaxial Silicon Transistor

Contents

Datasheet
Download this datasheet

PDF

e-mail this datasheet

[E-

This page Print version

Related Links

Request samples
How to order products
Product Change Notices (PCNs)
Support
Distributor and field sales representatives
Quality and reliability
Design tools

Features

- High BV_{CEO}

back to top

Applications

High Voltage General Amplifier
TV Video Output Amplifier

back to top

Product status/pricing/packaging

Product	Product status	Pricing*	Package type	Leads	Packing method
KSC2258AS	Full Production	$0.165	TO-126	3	BULK
KSC2258ASTU	Full Production	$0.165	TO-126	3	RAIL

* 1,000 piece Budgetary Pricing

back to top