

# SN54HC09, SN74HC09 QUADRUPLE 2-INPUT POSITIVE-AND GATES WITH OPEN-DRAIN OUTPUTS

D2804, MARCH 1984 — REVISED SEPTEMBER 1987

- Package Options Include Plastic "Small Outline" Packages, Ceramic Chip Carriers, and Standard Plastic and Ceramic 300-mil DIPs
- Dependable Texas Instruments Quality and Reliability

## description


These devices contain four independent 2-input AND gates. They perform the Boolean functions  $Y = A \cdot B$  or  $Y = \overline{A + B}$  in positive logic. The open-drain outputs require pull-up resistors to perform correctly. They may be connected to other open-drain outputs to implement active-low wired-OR or active-high wired-AND functions.

The SN54HC09 is characterized for operation over the full military temperature range of  $-55^{\circ}\text{C}$  to  $125^{\circ}\text{C}$ . The SN74HC09 is characterized for operation from  $-40^{\circ}\text{C}$  to  $85^{\circ}\text{C}$ .

FUNCTION TABLE (each gate)

| INPUTS |   | OUTPUT |
|--------|---|--------|
| A      | B | Y      |
| H      | H | H      |
| L      | X | L      |
| X      | L | L      |


## logic symbol†




†This symbol is in accordance with ANSI/IEEE Std 91-1984 and IEC Publication 617-12.

Pin numbers shown are for D, J, and N packages.

SN54HC09 . . . J PACKAGE  
SN74HC09 . . . D OR N PACKAGE  
(TOP VIEW)



SN54HC09 . . . FK PACKAGE  
(TOP VIEW)



NC--No internal connection

## logic diagram (positive logic)



2

HCMOS Devices

# SN54HC09, SN74HC09

## QUADRUPLE 2-INPUT POSITIVE-AND GATES

### WITH OPEN-DRAIN OUTPUTS

#### absolute maximum ratings over operating free-air temperature range†

|   |                |
|---|----------------|
| Supply voltage, $V_{CC}$ .....  | -0.5 V to 7 V  |
| Input clamp current, $I_{IK}(V_I < 0 \text{ or } V_I > V_{CC})$ .....       | $\pm 20$ mA    |
| Output clamp current, $I_{OK}(V_O < 0 \text{ or } V_O > V_{CC})$ .....      | $\pm 20$ mA    |
| Continuous output current, $I_O (V_O = 0 \text{ to } V_{CC})$ .....         | $\pm 25$ mA    |
| Continuous current through $V_{CC}$ or GND pins .....                       | $\pm 50$ mA    |
| Lead temperature 1,6 mm (1/16 in) from case for 60 s: FK or J package ..... | 300°C          |
| Lead temperature 1,6 mm (1/16 in) from case for 10 s: D or N package .....  | 260°C          |
| Storage temperature range .....   | -65°C to 150°C |

†Stresses beyond those listed under "absolute maximum ratings" may cause permanent damage to the device. These are stress ratings only, and functional operation of the device at these or any other conditions beyond those indicated under "recommended operating conditions" is not implied. Exposure to absolute-maximum-rated conditions for extended periods may affect device reliability.

#### recommended operating conditions

|          |  | SN54HC09         |          |      | SN74HC09 |      |     | UNIT |
|----------|--|------------------|----------|------|----------|------|-----|------|
|          |  | MIN              | NOM      | MAX  | MIN      | NOM  | MAX |      |
| $V_{CC}$ | Supply voltage                         | 2                | 5        | 6    | 2        | 5    | 6   | V    |
| $V_{IH}$ | High-level input voltage               | $V_{CC} = 2$ V   | 1.5      |      | 1.5      |      |     | V    |
|          |  | $V_{CC} = 4.5$ V | 3.15     |      | 3.15     |      |     |      |
|          |  | $V_{CC} = 6$ V   | 4.2      |      | 4.2      |      |     |      |
| $V_{IL}$ | Low-level input voltage                | $V_{CC} = 2$ V   | 0        | 0.3  | 0        | 0.3  | V   |      |
|          |  | $V_{CC} = 4.5$ V | 0        | 0.9  | 0        | 0.9  |     |      |
|          |  | $V_{CC} = 6$ V   | 0        | 1.2  | 0        | 1.2  |     |      |
| $V_I$    | Input voltage                          | 0                | $V_{CC}$ | 0    | $V_{CC}$ | V    |     |      |
| $V_O$    | Output voltage                         | 0                | $V_{CC}$ | 0    | $V_{CC}$ | V    |     |      |
| $t_t$    | Input transition (rise and fall) times | $V_{CC} = 2$ V   | 0        | 1000 | 0        | 1000 | ns  |      |
|          |  | $V_{CC} = 4.5$ V | 0        | 500  | 0        | 500  |     |      |
|          |  | $V_{CC} = 6$ V   | 0        | 400  | 0        | 400  |     |      |
| $T_A$    | Operating free-air temperature         | -55              | 125      | -40  | 85       | °C   |     |      |

#### electrical characteristics over recommended operating free-air temperature range (unless otherwise noted)

| PARAMETER | TEST CONDITIONS  | $V_{CC}$ | $T_A = 25^\circ\text{C}$ |           |            | SN54HC09 |            | SN74HC09      |     | UNIT |
|-----------|--|----------|--------------------------|-----------|------------|----------|------------|---------------|-----|------|
|           |  |          | MIN                      | TYP       | MAX        | MIN      | MAX        | MIN           | MAX |      |
| $I_{OH}$  | $V_I = V_{IH}$ or $V_{IL}$ , $V_O = V_{CC}$            | 6 V      | 0.01                     | 0.5       | 10         |          | .5         | $\mu\text{A}$ |     |      |
| $V_{OL}$  | $V_I = V_{IH}$ or $V_{IL}$ , $I_{OL} = 20 \mu\text{A}$ | 2 V      | 0.002                    | 0.1       | 0.1        |          | 0.1        | V             |     |      |
|           |  | 4.5 V    | 0.001                    | 0.1       | 0.1        |          | 0.1        |               |     |      |
|           |  | 6 V      | 0.001                    | 0.1       | 0.1        |          | 0.1        |               |     |      |
|           | $V_I = V_{IH}$ or $V_{IL}$ , $I_{OL} = 4$ mA           | 4.5 V    | 0.17                     | 0.26      | 0.4        |          | 0.33       |               |     |      |
|           | $V_I = V_{IH}$ or $V_{IL}$ , $I_{OL} = 5.2$ mA         | 6 V      | 0.15                     | 0.26      | 0.4        |          | 0.33       |               |     |      |
| $I_I$     | $V_I = V_{CC}$ or 0                                    | 6 V      | $\pm 0.1$                | $\pm 100$ | $\pm 1000$ |          | $\pm 1000$ | nA            |     |      |
| $I_{CC}$  | $V_I = V_{CC}$ or 0, $I_O = 0$                         | 6 V      |                          | 2         | 40         |          | 20         | $\mu\text{A}$ |     |      |
| $C_i$     |  | 2 to 6 V | 3                        | 10        | 10         |          | 10         | pF            |     |      |

**SN54HC09, SN74HC09**  
**QUADRUPLE 2-INPUT POSITIVE-AND GATES**  
**WITH OPEN-DRAIN OUTPUTS**

switching characteristics over recommended operating free-air temperature range (unless otherwise noted),  $R_L = 1\text{ k}\Omega$ ,  $C_L = 50\text{ pF}$  (see Note 1)

| PARAMETER | FROM (INPUT) | TO (OUTPUT) | $V_{CC}$ | $T_A = 25^\circ\text{C}$ |     |     | SN54HC09 |     | SN74HC09 |     | UNIT |
|-----------|--------------|-------------|----------|--------------------------|-----|-----|----------|-----|----------|-----|------|
|           |              |             |          | MIN                      | TYP | MAX | MIN      | MAX | MIN      | MAX |      |
| $t_{PLH}$ | A or B       | Y           | 2 V      | 60                       | 105 | 155 | 131      | ns  |          |     |      |
|           |              |             | 4.5 V    | 13                       | 25  | 36  |          |     |          |     |      |
|           |              |             | 6 V      | 10                       | 23  | 31  | 27       |     |          |     |      |
| $t_{PHL}$ | A or B       | Y           | 2 V      | 50                       | 100 | 150 | 125      | ns  |          |     |      |
|           |              |             | 4.5 V    | 10                       | 20  | 30  | 25       |     |          |     |      |
|           |              |             | 6 V      | 8                        | 17  | 25  | 21       |     |          |     |      |
| $t_f$     |              | Y           | 2 V      | 38                       | 75  | 110 | 95       | ns  |          |     |      |
|           |              |             | 4.5 V    | 8                        | 15  | 22  | 19       |     |          |     |      |
|           |              |             | 6 V      | 6                        | 13  | 19  | 16       |     |          |     |      |

|          |  |                                   |           |
|----------|--|-----------------------------------|-----------|
| $C_{pd}$ | Power dissipation capacitance per gate | No load, $T_A = 25^\circ\text{C}$ | 20 pF typ |
|----------|--|-----------------------------------|-----------|

NOTE 1: Load circuit and voltage waveforms are shown in Section 1.

**2**  
**HC MOS Devices**