



Linear Integrated Circuits

CA3000

DC Amplifier

Monolithic Silicon



- Designed for use in Communication, Telemetry, Instrumentation, and Data-Processing Equipment
- Balanced differential-amplifier configuration with controlled constant-current source to provide outstanding versatility
- Built-in temperature stability for operation from -55°C to +125°C
- Companion Application Note, ICAN 5030 "Applications of RCA CA3000 Integrated Circuit DC Amplifier" covers characteristics of different operating modes, frequency considerations, 10 MHz narrow band tuned amplifier design, crystal oscillator design, and many other application aids

HIGHLIGHTS

- Input Impedance 195 KΩ typ.
- Voltage Gain 30 dB typ.
- Common-Mode Rejection Ratio 98 dB typ.
- Input Offset Voltage 1.4 mV typ.
- Push-Pull Input and Output
- Frequency Capability
DC to 30 MHz (with external C and R)
- Wide AGC Range 90 dB typ.

APPLICATIONS

- Schmitt Trigger
- RC-Coupled Feedback Amplifier
- Mixer
- Comparator
- Modulator
- Crystal Oscillator
- Sense Amplifier




Fig. 1 SCHEMATIC DIAGRAM

92CS-12979R2

Resistance values are in ohms

ABSOLUTE-MAXIMUM VOLTAGE LIMITS, at $T_{FA} = 25^{\circ}C$

Indicated voltage limits for each terminal can be used under specified voltage conditions for other terminals

All voltages are with respect to ground (common terminal of Positive and Negative DC Supplies)

TERMINAL	VOLTAGE LIMITS		CONDITIONS	
	NEGATIVE	POSITIVE	TERMINAL	VOLTAGE
1	-2	+2	2	0
			3	-6
			6	0
			9	+6
2	-8	0	1	0
			3	-8
			6	0
3	-10	0	1	0
			2	0
			6	0
4	-8	0	1	0
			2	0
			6	0
5	-6	0	1	0
			2	0
			3	-6
			6	0
			9	+6

TERMINAL	VOLTAGE LIMITS		CONDITIONS	
	NEGATIVE	POSITIVE	TERMINAL	VOLTAGE
6	-2	+2	1	0
			2	0
			3	-6
			9	+6
7	NO CONNECTION			
8	0	+6	1	0
			2	0
			3	-6
			6	0
9	0	+10	1	0
			2	0
			3	-6
			6	0
10	0	+6	1	0
			2	0
			3	-6
			6	0
CASE	Internally Connected to Terminal No.3 (Substrate) DO NOT GROUND			

OPERATING-TEMPERATURE RANGE $-55^{\circ}C$ to $+125^{\circ}C$
 STORAGE-TEMPERATURE RANGE $-65^{\circ}C$ to $+150^{\circ}C$
 LEAD-TEMPERATURE (During Soldering):
 At distance $1/16 \pm 1/32$ inch (1.59 ± 0.79 mm)
 from case for 10 seconds max. $+265^{\circ}C$

MAXIMUM SINGLE-ENDED INPUT-SIGNAL VOLTAGE . . . ± 4 V
 MAXIMUM COMMON-MODE INPUT-SIGNAL VOLTAGE . . . ± 2 V
 MAXIMUM DEVICE DISSIPATION:
 From $-55^{\circ}C$ to $85^{\circ}C$ 450 mW
 Above $85^{\circ}C$ Derate 5 mW/ $^{\circ}C$

STATIC CHARACTERISTICS AND TEST CIRCUITS FOR TYPE CA3000

INPUT OFFSET VOLTAGE AND CURRENT vs TEMPERATURE




Fig.2

92CS-13299

INPUT BIAS CURRENT vs TEMPERATURE




Fig.3

92CS-13296

ELECTRICAL CHARACTERISTICS, at $T_{FA} = 25^{\circ}C$, $V_{CC} = +6V$, $V_{EE} = -6V$, unless otherwise specified

CHARACTERISTICS	SYMBOLS	SPECIAL TEST CONDITIONS Terminals No.4 & No.5 Not Connected Unless Specified	TEST CIRCUITS	LIMITS					TYPICAL CHARAC- TERISTICS CURVES Fig.
				TYPE CA3000					
				Fig.	Min.	Typ.	Max.	Units	
STATIC CHARACTERISTICS									
Input Offset Voltage	V_{IO}			-	1.4	5	mV	2	
Input Offset Current	I_{IO}			-	1.2	10	μA	2	
Input Bias Current	I_{IB}			-	23	36	μA	3	
Quiescent Operating Voltage	V_8 or V_{IO}	TERMINALS							
		4	5						
		NC	NC	-	2.6	-	V	4	
		NC	VEE	-	4.2	-	V	4	
		VEE	NC	-	-1.5	-	V	4	
VEE	VEE	-	0.6	-	V	4			
Device Dissipation	P_D	NC	NC	-	30	-	mW	NONE	
DYNAMIC CHARACTERISTICS									
Differential Voltage Gain Single-Ended Input	A_{DIFF}	Single-Ended Output $f = 1$ kHz		9	28	32	-	dB	5
		Double-Ended Output $f = 1$ kHz		9	-	38	-	dB	5
Bandwidth at -3 dB Point	BW	$V_I = 10$ mV, $R_S = 1$ k Ω		-	650	-	kHz	7	
Maximum Output Voltage Swing	$V_{OUT(P-P)}$	$f = 1$ kHz		9	-	6.4	-	V(P-P)	NONE
Common-Mode Rejection Ratio	CMRR	$f = 1$ kHz		13	70	98	-	dB	8
Single-Ended Input Impedance	Z_{IN}	$f = 1$ kHz		15	70K	195K	-	Ω	10
Single-Ended Output Impedance	Z_{OUT}	$f = 1$ kHz		17	5.5K	8K	10.5K	Ω	12
Total Harmonic Distortion	THD	$R_S = 1k\Omega$ $f = 1$ kHz $V_O = 42V_{P-P}$		-	0.2	5	-	%	14
AGC Range (Maximum Voltage Gain to Complete Cutoff)	AGC	$f = 1$ kHz		20	80	90	-	dB	NONE

QUIESCENT OPERATING VOLTAGE vs TEMPERATURE




Fig. 4

92CS-13394

DYNAMIC CHARACTERISTICS AND TEST CIRCUIT FOR TYPE CA3000

DIFFERENTIAL VOLTAGE GAIN vs TEMPERATURE




Fig.5

92CS-13594

DIFFERENTIAL VOLTAGE GAIN AND MAXIMUM OUTPUT VOLTAGE SWING TEST CIRCUIT




Fig.6

92CS-13497R1

BANDWIDTH AT -3 dB POINT vs TEMPERATURE




Fig.7

92CS-13294

COMMON-MODE REJECTION RATIO vs TEMPERATURE




Fig.8

92CS-13297

COMMON-MODE REJECTION RATIO TEST CIRCUIT




Fig.9

92CS-12983R2

SINGLE-ENDED INPUT IMPEDANCE vs TEMPERATURE




Fig.10

92CS-13298

COMMON-MODE REJECTION RATIO (CMR) = 20 log $\frac{A^*(2)(0.3)}{E_d(RMS)}$
 *A = SINGLE-ENDED VOLTAGE GAIN AS MEASURED IN CIRCUIT SHOWN IN FIG.6B

DYNAMIC CHARACTERISTICS AND TEST CIRCUITS FOR TYPE CA3000

SINGLE-ENDED INPUT IMPEDANCE TEST CIRCUIT




Fig. 11

92CS-13498RI

SINGLE-ENDED OUTPUT IMPEDANCE vs TEMPERATURE




Fig. 12

92CS-1330I

SINGLE-ENDED OUTPUT IMPEDANCE TEST CIRCUIT




Fig. 13

92CS-13455RI

TOTAL HARMONIC DISTORTION vs TEMPERATURE




Fig. 14

92CS-13495

AGC RANGE TEST CIRCUIT




Fig. 15

92CS-13449RI